



### Auto Wire Harness Rubber Cable Sleeve

KINGTOM is a major manufacturer and supplier of rubber products in China. Auto Rubber Cable Sleeve in the car wiring harness is very common, the rubber sleeve has no fixed shape, it is set according to the needs of all kinds of cars, the most important thing is to reflect the importance of its immersion.

KINGTOM is a major manufacturer and supplier of rubber products in China.

**Auto Rubber Cable Sleeve** in the car wiring harness is very common, the rubber sleeve has no fixed shape, it is set according to the needs of all kinds of cars, the most important thing is to reflect the importance of its immersion.

#### Product Parameter of the **Auto Wire Harness Rubber Cable Sleeve**:

- ①Product name: **Auto Wire Harness Rubber Cable Sleeve**
- ②Material: EPDM NBR Silicon or Can Custom
- ③Logo: Can Custom
- ④Size: Can Custom
- ⑤Can Custom: Black or custom
- ⑥Application: Automotive
- ⑦Certifications: IATF16949 ,ISO14001:2015,ROHS,CMC, etc
- ⑧Delivery: 30 -50days after sample confirmation
- ⑨Sample: 25-30 days
- ⑩Payment: 30% deposit, 70% payment before shipment
- ⑪Package: PE bags, Cartons,Pallet
- ⑫Payment Terms: T/T,L/C and so on.
- ⑬Shipment Way: Vessel,Air,Express etc.

**Product Feature AND Application of the Auto Wire Harness Rubber Cable Sleeve:**

**Black rubber cable sleeve** is a rubber metal ring that is arranged in the connecting parts of the wiring harness and the automobile body. Its function is to prevent the hole from water and protect the wire harness at the edge of the metal hole. Below is the characteristics of rubber sleeve:

- ① Embedded, used under the condition of ensuring the working posture and installing confirmation; Tension is weak in the opposite direction of installation.
- ② Pull out test, under the condition of ensuring the pull out working posture and installation confirmation: insert force opposite to the installation direction is weak.
- ③ The door is used between the car body and the door. In order to strengthen the extension of the door when it opens and closes, the middle part adopts the shape of snake belly: it is generally pulled out from the side of the body and inserted into the side of the door.
- ④ Plastic fastener, in order to make the rubber sleeve can be quickly inserted into the body, and in the body side rubber sleeve is configured with resin products; Not fully waterproof.
- ⑤ Screw fixed, used from the engine room to the indoor through the operation posture is not good or through the hole is not round; There is a gap between the body and the plane of the rubber sleeve iron sheet will be soaked: the metal parts of the rubber sleeve will scratch the wire harness, and there is no scalability, affecting the elongation of the wire harness



